

PEÑAMADER MATT

Page 1 de 2

Varnish alkyd of very high quality, with a soft touch, matte finish, great penetration and high power of wood protection, especially for the protection of wood inside, and can be also applied on outside but in areas not directly exposed to the sun.

Features

Specific weight	0,92 gr/cc.
Viscosity	63" (Cup Ford nº 4)
Fixed material	48%
Drying time at touch	4 hours
Repainting	24 hours
Finishing	Matte
Type of carrier	Alkyd resin (not yellowish)
Packaging	375 ml, 750 ml and 4 lt. container
Color	Colorless



Application

Theoric performance	7 - 9 m ² /l according the state of the surface
Solvent	Universal
Number of components	1
Method of application	Brush, roller, spray gun

Preparation of the surface

Variations of temperature, humidity, thickness, etc., may cause changes in drying, performance, etc. The surface must be dry and clean, free from grease, dust and dirt. It is recommended to apply at least 2 coats, diluted first so that it penetrates well in wood and the second viscosity of supply. **UV** inhibitor

Suitable for use domestic, not suitable for children.







Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.











PEÑAMADER MATT

Page 2 de 2

pinturas de la peña fábrica de pinturas



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com









