

BASE 1 SATIN (WHITE)

Special Acrylic Satin Paint for Dyeing System (Mix machine)

Page 1 de 2

pinturas de la peña fábrica de pinturas

The acrylic paint BASE 1 SATIN is formulated with emulsions most advanced and first quality, as well as other raw materials, which gets a great product of high performance, hardness, perfect coverage for its wealth of dioxide of titanium and good resistance to weather and rubbing, by its great amount of emulsion.

BASE 1 SATIN acrylic paint, possesses great flexibility, good adhesion and resistance to the alkalinity of the cement, it is vapor-permeable indoor and waterproof to the outdoor, and also has a great power covering, leaving a perfect finish.

It is specially formulated, tested and calibrated to obtain pastel intensity colors in the tintometric system of La PEÑA.





Color	White
Finishing	Satin
Specific weight	1,28 +/-0,05 gr./cc.
Viscosity at time of packaging	100 K.U. to 25 ℃
Fixed material	50 % +/- 1
Performance	10 - 12 m ² /Kg
Drying time at touch	45 minutes
Treat	21 days
Repainting	4 hours
Diluent	Water (10 - 20 %)
Packaging	1, 5 and 18 Kg containers
Conservation	Keep away from extreme temperatures

Application

It is an also indicated product outdoors and indoors, it can be applied to cement, plaster, concrete, brick, stone, etc. It is particularly suitable as white base coloring in any painting system that is based on two or three bases. Brush, paint roller or "Airless" spray gun. The surfaces must be clean and dry. Don't apply under temperatures lower than 5°C or higher than 35°C.

Composition

Water, emulsions, dioxide of titanium, calcium carbonate and other materials chosen for this product.

Suitable for use domestic, not suitable for children.

Cautions

S2 Keep out of reach of children


S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.


S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.













fábrica de pinturas

BASE 1 SATIN (WHITE)

Special Acrylic Satin Paint for Dyeing System (Mix machine)

Page 2 de 2



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

