

fábrica de pinturas

PEÑAMADER GLOSS

Glossy varnish for wooden Indoor - Outdoor

Page 1 de 2

Varnish alkyd of very high quality, with a soft touch, very high brightness, high penetration and high power of wood protection, especially for the protection of woods exposed to weather.



Features

Specific weight	0,92 gr/cc.
Viscosity	63" (Cup Ford nº 4)
Fixed material	48%
Drying time at touch	4 hours
Repainting	24 hours
Finishing	High Shine
Type of carrier	Alkyd resin (not yellowish)
Packaging	375 ml, 750 ml and 4 lt. container
Color	Colorless

Application

Theoric performance	7 - 9 m ² /I according the state of the surface
Solvent	Universal
Number of components	1
Method of application	Brush, roller, spray gun

Preparation of the surface

Variations of temperature, humidity, thickness, etc., may cause changes in drying, performance, etc. The surface must be dry and clean, free from grease, dust and dirt. It is recommended to apply at least 2 coats, diluted first so that it penetrates well in wood and the second viscosity of supply.

UV inhibitor


Suitable for use domestic, not suitable for children.








Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.











pinturas de la peña fábrica de pinturas

PEÑAMADER GLOSS

Glossy varnish for wooden Indoor - Outdoor

Page 2 de 2



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

> www.delapenia.com Factory and offices

