pinturas de la peña
fábrica de pinturas

RUGOPEÑA SMOOTH

Indoor/Outdoor Anticarbonation Smooth Coating

Anticarbonation coating paint, manufactured using copolymers in emulsion, titanium dioxide and other fillers with a mixture of the appropriate granulometry. It can be applied indoor and outdor and it leaves a slightly rough matt finish. RUGOPEÑA SMOOTH is of excellent quality, a good whiteness and great covering power.
Its formulation has been specially designed for the protection and decoration of external walls of mortar, cement, brick, plasters, etc. All colours have the highest resistance to light and to outdoors conditions.
This paint was submitted to trials according to UNE-EN 1504-2:2005 standard for "Protection systems for concrete surfaces" by Applus (+) laboratories.

Features



Color	White and other colors of the chart
Finish	Smooth Matt
Specific weight	1,70 +/- 5 gr./cc.
Viscosity at time of packaging	105 K.U. +/- 5 to 25 ºC
Fixed matter %	65%
Performance	4 - 6 m^2/kg
Wet film recommended thickness	100 microns per coat
Dry film recommended thickness	40 - 44 microns per coat
Dry-to-touch time	4 - 6 hours
Curing time	21 days
Recoat	6 - 8 hours
Thin with	Clean water, so it is considered fireproof
Presentation	5 kg and 23 kg cans
Conservation	Keep away from extreme temperatures
VOC	Cat A/c (legal limit 40 g/L). Max. cont. 25 g/L

Technical information

Adherence by direct tensile method	2.9 MPa (UNE-EN 1542:1999)
Perméabilité sous la vapeur d'eau	Sd: 0.30 m (UNE –EN ISO 7783-2:1999)
Permeabilité à l'eau liquide	W = 0. 09 Kg/m^2*h 0.5. Low (UNE EN 1062-3:2008)
Perméabilité au CO2	Sd: 50.9 m (UNE EN 1062-6:2003)
Résistance à l'impact	24.5 Nm (UNE EN ISO 6272-1:2004)
Résistance à l'abrasion TABER 100-1000 cycles	Reduction poids 40% (EN-ISO-5470-1)

Application

Blend the product until it is perfectly mixed. It can be applied by brush, roller or spray. It is highly recommendable to give at least two coats for the correct waterproofing and protection of the surface (first coat diluted in fresh water at 15-20% and the second at 5-10%). Surfaces to be painted must be clean and dry, and free of dirt, dust, grease, oil, rust, soap, wax, scaling paint, water soluble materials, and mildew. Do not apply when air and surface temperatures are below 5° C or above 35º C. Air humidity should be under 80%. Do not apply outdoors with rain forecast for the following 8 hours or frost forecast for the following 48 hours.

Composition

Water, dioxide titanium, carbonates and other fillers, emulsions and additives of high quality.

Distribuidor Oficial de :
GRACO FESTOOL

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

Trofeo CC100 Compromiso a la Calidad

Factory and offices
Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

Master Internacional de Empresas

Suitable for domestic use. Keep out of reach of children.

Cautions

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.

EUH208 Contains 2-octyl-2H-isothiazon-3-one.
Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one [EC no. 247-500-7]; 2-methyl.2H-isothyazol-3-one [EC no. 220-239-6] (3:1).
May produce an allergic reaction.

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.

Distribuidor Oficial de : FESTOOL GRACO

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

Factory and offices

Trofeo CC100 Compromiso a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f : +34 925 341 082
e: info@delapenia.com

Master Internacional de Empresas

pinturas de la peña
fábrica de pinturas

RUGOPEÑA SMOOTH

Indoor/Outdoor Anticarbonation Smooth Coating

Distribuidor Oficial de :
GRACO FESTOOL

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

Factory and offices

Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f : +34 925 341 082
e: info@delapenia.com

Master
Internacional
de Empresas