

fábrica de pinturas

## **SEMIBRIGHT 5000-P ACRYLIC PAINT**

High Performance and Durability Acrylic Paint

Page 1 de 2

5000-P is a suitable paint for inside as well as for outside, which possesses a very high covering power and whiteness and a great resistance to the sun and to the weather. It's elaborated with quality products plus fungicides and antirust, that make it good for protection against mould and antibacterial action. It also has a strong adhesion, so it can be applied on the plate or iron with a previous work with primer. 5000-P is formulated with silicone additives that give it water-repellent properties.

#### **Features**



reatures	
Color	White
Finishing	Bright medium
Specific weight	1,29 +/- 0,05 gr./cc.
Viscosity on having tippled	90 K.U. to 25 ℃
Fixed material %	60 % +/- 5
Solid in volume %	46 % +/- 5
Performance	10 to 12 m <sup>2</sup> /Kg. per coat depending of the state of the surface
Minimum recommended	28-32 microns per coat
thickness	
Time of drying at touch	40 - 60 minutes
Treat	21 days
Repainting	4 - 6 hours minimum, maximum without limit
Diluent	Fresh water
Presentation	Containers in 5 and 20 Kg.
Conservation	Keep away from extreme temperatures
COV'S	Cat A/a (legal limit 100 g/l) max. cont. 30 g/l

### **Application**

Brush, paint roller or spray gun. The surfaces must be clean and dry. Don't apply under temperatures below 5°C or higher than 35°C.

#### **Composition**

Water, acrylic pure emulsion, dioxide of titanium, calcium carbonate and other raw materials chosen for his product.

#### THIS PAINTING HAS PASSED THE GEOCISA LABORATORIES QUALITY CONTROLS

Suitable for use domestic, not suitable for children.

#### **Cautions**

S2 Keep out of the reach of children

S23/24/25 Do not breathe vapours and avoid contact with eyes and skin.

Use only in well-ventilated areas.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or quarantee nor object of responsibility.





t: +34 925 300 409 f: +34 925 341 082 e: info@delapenia.com







fábrica de pinturas

# **SEMIBRIGHT 5000-P ACRYLIC PAINT**

High Performance and Durability Acrylic Paint

Page 2 de 2



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com





