



pinturas de la peña
fábrica de pinturas

WATERBORNE POLYURETHANE VARNISH

Waterborne Polyurethane Varnish for Passable Floors

Page 1 de 2

Polyurethane varnish base water with high performance and specially designed for a longer protection of mineral floorings. It can be used directly or catalyzed if you want a higher chemical and mechanical resistance.

It has high resistance to stains, highly resistant to chemical attack, and high abrasion resistance. Easy and fast to apply. It can be used for the protection of all types of flooring, indoors and outdoors. Gives long-lasting protection forming a highly abrasion-resistant protective layer reducing dirt and pavement maintenance times.

Features



BASE (COMP. A)	
Color	Transparent
Finishing	Glossy
Specific weight	1,05 +/-0,03 gr./cc.
Solid in volume	31 % +/- 1
Viscosity at time of packaging	80 K.U. to 25 °C
Performance	8 - 10 m ² /Kg. on depending of the state of the walls
Life of mix	120 Minutes
Walkable	24 hours
Pissable	48 hours
Treat	7 - 8 days
Repainting	12 hours
Diluent and clean of tools	Water
Packaging	4 and 14 Lt containers
Conservation	Keep away from extreme temperatures
HARDENER (COMP. B)	
Colour	Transparent
Specific weight	1,10 +/-0,05 gr./cc.

Application

It can be applied by brush or roller to short hair. To paint walls must be clean, dry, and well consolidated. Do not apply to stands below 10°C over 30°C, and the air humidity should be less than 80%.

If you want the highest chemical and mechanical resistance is used catalyzed form:

Add hardener (Comp. B) to the base (Comp. A), mixing them by hand or with mechanical stirrer of low rpm (to not produce foam) until you get a perfect homogenization. Wait 3 to 5 minutes approximately before you begin your application.

Once product is ready for use mixed, do not dilute. The application of two crossed hands is recommended. Within 24 hours it is passable with caution, maximum hardness reaches approximately 7 days.

Suitable for use domestic, not suitable for children.

Cautions

S2	Keep out of reach of children
S23/24/25	Do not breathe vapors and avoid contact with eyes and skin.
S51	Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

WATERBORNE POLYURETHANE VARNISH

Waterborne Polyurethane Varnish for Passable Floors

Page 2 de 2



Distribuidor Oficial de :

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

Master
Internacional
de Empresas

