



pinturas de la peña
fábrica de pinturas

ACRYLIC MATT PAINT MATE EXTRA

Interior and Exterior Acrylic Matt Paint

Page 1 de 2

MATE EXTRA acrylic matt paint is formulated with advanced technology emulsions that result in a product of high quality, high performance and good resistance to weather.

It has great flexibility, good adhesion and resistance to the alkalinity of the cement. It is permeable to interior vapours and waterproof to the exterior ones. It is a product indicated to paint both indoor and outdoor (*).

In its formulation we use last generation fungicide, algacide and bactericide additives, that confer it resistance to mildew, algae, fungi, etc. As a result, the paint remains unaltered over the years.

Features



Color	White and colors according to colour chart (*)
Finish	Matt
Specific weight	1,62 gr./cc.
Viscosity on time of packaging	115 K.U. at 25° C
Fixed matter %	66 % +/- 1
Performance	8 - 10 m ² /kg per coat depending on the state of the surface
Wet film recommended thickness	60 - 70 microns per coat
Dry film recommended thickness	25 - 30 microns per coat
Dry-to-touch time	40 - 60 minutes
Curing time	21 days
Recoat	8 to 10 hours minimum. Maximum without limit
Thin with	Clean water
Presentation	1, 5, 10 and 23 kg cans
Conservation	Keep away from extreme temperatures
VOC's	Cat A/a (legal limit 30 g/l). Maximum content 25 g/l

Application

It can be applied on any material of construction: plaster, cement, brick, stone, etc. It can be applied by brush, roller or sprayed. Surfaces to be painted must be completely clean and dry. Do not apply when air and surface temperatures are below 5° C or above 35° C.

Formula

Water, emulsions, titanium dioxide, calcium carbonate and other fillers specifically chosen for this product.

Suitable for domestic use. Keep out of reach of children.

Cautions

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.

EUH208 Contains 2-octyl-2H-isothiazon-3-one. Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one [EC no. 247 500-7]; 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com



Master
Internacional
de Empresas



pinturas de la peña
fábrica de pinturas

ACRYLIC MATT PAINT MATE EXTRA

Interior and Exterior Acrylic Matt Paint

Page 2 de 2

(*) In strong colors, please consult us about its stability outdoors.

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com



Master
Internacional
de Empresas