

PEÑA AKRIL MATT, plastic painting of an unequalled whiteness, of great hardness and resistance to the wet rub, so it is perfect for exterior and interior and at the same time of great decoration.

PEÑA AKRIL MATT is manufactured with great care and raw materials subjected to the strictest quality controls, so, it can be said that it is a matt-silky plastic paint unsurpassed by its whiteness, covering power, resistance to indoor and outdoor environments. It also contains fungicide, which prevents the appearance of scum and mildew stains.

It can be applied to any building material, plaster, cement, etc.

### Features

Color	White
Finish	Matt silky
Specific weight	1,64 +/-0,05 gr./cc.
Viscosity at time of packaging	105 K.U. a 25°C
Fixed matter %	70% +/- 5
Volumen solids %	43% +/- 5
Gardner washability	> 8.000 ddp
Performance	8 - 10 m <sup>2</sup> /kg per coat, depending on the state of surface
Dry film recommended thickness	25-30 micras per coat
Drying time to touch	40 - 60 minutes
Total curing	21 days
Recoat	4 -6 hours minimum, maximum without limit
Diluent	Clean water
Presentation	Cans of 5, 10 and 20 kg
Conservation	Keep away from extreme temperatures
COV'S	Cat A/a ( legal limit 30 g/l) contenido max 25 g/l



### Application

It can be applied on any building material, plaster cement, etc. Its application can be brushed, roller or sprayed. Before application the facing must be completely clean and dry, taking into account that it should not be applied at temperatures below 5 °c or above 35 ° C.

### Composition

Water, aqueous emulsions, titanium dioxide, high quality additives and the best loads.

### PAINTING SUBMITTED TO TESTS BY THE GEOCISA LABORATORIES.

**Suitable for domestic use. Keep out of reach of children.**

### Cautions

- P101 If medical advice is needed, have the container or label handy.
- P102 Keep out of reach of children.
- P103 Read the label before use.
- P501 Delete the content and/or its container through the selective collection system enabled in your municipality.



*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

[www.delapenia.com](http://www.delapenia.com)

Fábrica y oficinas



Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)





pinturas de la peña  
fábrica de pinturas

## PEÑA AKRIL MATT®

Matt Plastic paint for demanding smooth

Page 2 of 2

EUH208 Contents 2-octil-2H-isotiazon-3-ona.

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-ona [EC No. 247-500-7]; 2-methyl. 2h-Isothiazol-3-ona [EC No. 220-239-6] (3:1) may cause an allergic reaction.

*According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.*



Distribuidor Oficial de:

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**[www.delapenia.com](http://www.delapenia.com)**

Fábrica y oficinas



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)



Master  
Internacional  
de Empresas